

TUF GAMING VG279QL1A MONITOR



KEY FEATURES



High refresh rate for



125% s<mark>RGB</mark>

ultra fast and smooth gameplay



Fast paced gaming experience with

ghosting free



VESA DisplayHDR 400 certified to reproduce lifelike images

With superior image

quality and provides

wide viewing angle


Shadow Boost

ELMB




Reduce motion blur to create smooth gameplay

To enhance the details in dark scenes



Stereo speakers to enjoy multimedia contents







TUF Gaming VG279QL1A has undergone stringent performance tests and is certified Flicker-free and Low Blue Light by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services.



TUF GAMING VG279QL1A MONITOR

Display	Panel Size (diagonal)	27"(68.5cm) Wide Screen (16:9)
	Display Viewing Area	597.888(H) x 336.312(V)
	Panel Backlight/ Type	WLED / IPS
	Display Surface	Non-glare
	True Resolution	1920x1080
	Pixel Pitch	0.311mm
	Brightness (Max.)	400 cd/m2 (HDR)
	Contrast Ratio (Max.)	1,000:1
	Viewing Angle (CR≥10)	178 (H) / 178 (V)
	Color saturation	125% sRGB/DCI-P3 95%
	Display Colors	16.7M
	Response Time	1ms MPRT (2ms GTG)
	Refresh rate	165Hz
	Flicker Free	Yes
	HDR	DisplayHDR 400
Video Features	ELMB	Yes
	HDCP	Yes
	GameVisual	Yes (FPS,RTS/RPG, Racing , sRGB, Cinema, Scenery, MOBA)
	GamePlus	Yes (Crosshair, Timer, FPS Counter, Display Alignment)
	Low Blue Light	Yes
Input / Output		DisplayPort1.2 x1, HDMI (v2.0) x2, earphone jack (3.5 mini-jack)
Speaker		2W x 2 stereo, RMS
Signal Frequency		DP: 200KHz to 200KHz(H)/48Hz to 165Hz(V) HDMI:30KHz to 200KHz(H)/48HZ to 165Hz(V)
Power	Power Consumption	< 18 W*
	Voltage	100–240V, 50 / 60 Hz
Mechanical Design	Tit	-5° ~23° mm
	Swivel	+15°~-15° mm
	Pivot	+90°~-90° mm
	Height Adjustment	120mm
Dimension	Phy. Dimension	614.09x (413.65~533.65) x213.79mm (with stand) 614.09 x 364 x 56.95 mm (without stand) 730x441x224 mm (box)
Weight	6.2kg (net), 9.5kg (gross), 3.9kg (Net Weight without Stand)	
Special Features	Shadow Boost, ELMB, FreeSync Premium technology, 1ms MPRT, DisplayWidget Lite	
Accessories	Power cord, Power adapter(65W), Warranty card , QSG, HDMI cable(option), DP cable(option)	
Compliance and Standards	TUV-Flicker Free, TUV-Low Blue Light, DisplayHDR 400	

*1ms MPRT spec is based on internal testes. Response time may vary depending on test conditions ** measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

