

24X Internal **DVD** Writer DRW-24D5MT

ASUS DRW-24D5MT is a 24X DVD writer with M-DISC support for lifetime data backup. It is the drive for users who are looking for additional data protection, energy efficiency and faster burning rates.

FEATURES

M-DISC Support Save users' data for up to 1,000 years

Disc Encryption*

Protect users' data with password control and encoded file name functionality

Nero BackItUp* Full backup for your devices

and BULK with Software versions



SPECIFICATIONS

Black Read Speed DVD±R: 16X DVD+R(SL, M-DISC): 12X DVD+RW: 13X DVD-RW: 8X DVD-ROM: 16X DVD±R(DL): 12X DVD-ROM(DL): 12X DVD-RAM: 5X CD-R: 48X CD-RW: 40X CD-ROM: 48X DVD-Video Playback: 6X Audio CD Playback: 10X Write Speed

Color

DVD+R· 24X DVD+R(SL, M-DISC): 4X DVD+RW: 8X DVD-RW: 6X

DVD±R(DL): 8X DVD-RAM: 5X CD-R· 48X

CD-RW: 24X

Access Time (Random)

DVD: 145 ms CD: 125 ms

O/S Compatibility Windows® 11/10/8.1

Bundled Software (For Wind CyberLink Power2Go 8* CyberLink PowerBackup 2.6* Nero BackItUp* E-Green

*Only available on Retail Box and BULK with Software versions

Writing Mode

(1) DVD-R: Disc at Once and Incremental Recording (2) DVD-R DL: Disc at Once and Incremental Recording (3) DVD-RW: Disc at Once, Incremental Recording and Restricted Overwriting (4) DVD-RAM: Random Recording (5) DVD+R: Sequential Recording (6) DVD+R DL: Sequential Recording (7) DVD+RW: Random Recording (8) CD-R/RW: Disc at Once, Session at Once, Track at Once and Packet Recording System Requirement CPU: Intel® Pentium® 300 MHz or higher RAM: 128 MB or more is recommended HDD: 10 GB or more Disc Formats Reading:

DVD±R(SL/DL), DVD±RW, DVD-ROM(SL/DL), DVD-RAM, DVD-Video, CD-R, CD-RW, CD-ROM, Audio CD, VCD, CD-I, CD-Extra, Photo CD, CD-text, CD-ROM/XA, Multi-session CD Writing

DVD±R(SL/DL), DVD±RW, DVD-RAM, CD-R, CD-RW

Configurations

Dimensions 170 x 146 x 41 mm (L/W/H)

Weight 600 ± 50 g

Interface

SATA Disc Diameters

12 cm and 8 cm

Electrical and Environmental Specifications

Power Requirement DC+5V ±5%, DC+12V ±10 % Temperature

Operating: 5°C to 40°C Storage: -30°C to 60°C Humidity

Operating: 15%~85%(Non-condensing) Storage: 10%~90%(Non-condensing)

*This feature is only available on Retail Box

