

## PANEL

Screen Size	55" (54.64" Measured Diagonal)
Resolution	1,920 x 1,080 (FHD)
Brightness (Typ., cd/m <sup>2</sup> )	2500

## CONNECTIVITY

Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, External Speaker (L/R)
External Control	RS232C In/Out, RJ45 In, IR Receiver In

## PHYSICAL SPECIFICATION

Bezel Width	12.0 mm (T/B), 9.9 mm (L/R)
Monitor Dimension (W x H x D)	1,235.5 x 709.4 x 85.4 mm
Weight (Head)	24.7 kg
Carton Dimensions (W x H x D)	1,360 x 231 x 844 mm
Packed Weight	29.9 kg
VESA™ Standard Mount Interface	600mm x 400mm

## POWER

Power Type	Built-In Power
Power Supply	100-240V~, 50/60Hz

## POWER CONSUMPTION

<b>Typ./Max</b>	240 W / 270 W
-----------------	---------------

---

<b>Smart Energy Saving</b>	120 W
----------------------------	-------

---

## STANDARD(CERTIFICATION)

<b>Safety</b>	CB / NRTL
---------------	-----------

---

<b>EMC</b>	FCC Class "A" / CE / KC / VCCI
------------	--------------------------------

---

<b>ErP / Energy Star</b>	Yes (EU Only) / No
--------------------------	--------------------

---

## SOFTWARE COMPATIBILITY

<b>Content Management Software</b>	SuperSign CMS
------------------------------------	---------------

---

<b>Control and Monitoring Software</b>	SuperSign Control+ (Software compatibility may change over time.)
--	--

---

## ACCESSORY

<b>Basic</b>	Remote Controller, Power Cord, HDMI Cable, Manual (ESG/EIG), IR Receiver (w/ Ambient Light Sensor)
--------------	---

---

<b>Optional</b>	Landscape Wall Mount (WM-L640V), Portrait Wall Mount (WM-P640V), Wi-Fi Dongle (AN-WF500)
-----------------	---

---