

ProArt Display PA147CDV

Your creative workflow, dialed up



GOOD DESIGN
AWARD 2021



reddot winner 2022



COMPUTEX
d&i gold awards 2021



calman
VERIFIED



Key Features



Ultra-wide

32:9 ultra-wide Full HD (1920 x 550) IPS anti-glare pane



International color standard
100% sRGB / 100% Rec. 709
color space for digital images
and video production



Factory pre-calibrated with
ASUS advanced gray-scale
tracking technology to
guarantee the ΔE color
difference value is less than 2



With MPP 2.0 support, you're
able to use whip out a pen or
stylus to jot down or sketch
ideas whenever inspiration
strike*



10-point Touch

Capacitive 10-point multi-touch
capability and Windows 10
compatible**

HDMI™



USB Type-C
Monitor

Dual USB-C and HDMI ports
provide rich connectivity



Control Panel

Virtual Control Panel Integrate
Software provides shortcut
and customized hotkey to
enhance productivity***



ASUS Dial

Intuitive ASUS Dial control
integrate software and support
Microsoft Dial provides shortcut
and customized hotkey to
enhance productivity***



Ergo Kick Stand

Ergo Kick Stand design
provides intuitive tilt angle
adjustment with landscape and
portrait view

*ASUS Pen or stylus not included.


**10-point touch function will depend on the operating system.

***ProArt Creator Hub (ASUS Dial and Control Panel function) support Microsoft Windows only.

ASUS

ProArt Display PA147CDV

Spec Sheet

Display	Panel Size : 14-inch (35.56cm) Wide Screen (32:9) Display Viewing Area(HxV) : 344.22 x 98.60 mm Display Surface : Non-Glare Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.179mm Resolution : 1920x550 Color Space (sRGB) : 100% Color Space (Rec.709) : 100% Brightness (Typ.) : 400cd/m² Contrast Ratio (Typ.) : 1200:1 ASUS Smart Contrast Ratio (ASCR) : 100000000:1 Display Colors : 16.7M Response Time : 5ms (GTG) Refresh Rate (Max) : 60Hz Flicker-free : Yes Touch Screen : Yes, Capacitive 10-point multi-touch
Video Feature	Trace Free Technology : Yes ProArt Preset : Standard / sRGB / DCI-P3 / Rec. 709 / Scenery / Reading / Darkroom / User mode1 / User mode2 Color Temp. Selection : Yes (5 modes) Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y) Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes QuickFit : Yes HDCP : Yes, 1.4 Low Blue Light : Yes
Audio Feature	Speaker : Yes (1Wx2)
IO ports	USB-C x 2 HDMI(v1.4) x 1 HDMI(v1.4) USB-C USB-C 
Signal Frequency	Digital Signal Frequency : 24 KHz~83 KHz (H) / 23 Hz~60 Hz (V)
Power Consumption	Power On (Typical): < 10W Power Saving Mode : < 0.5W 100-240V, 50/60Hz
Mechanical Design	Tilt : 25° ~ 70° Pivot : 90° (Clockwise)
Dimensions (Est.)	Phys. Dimension with Stand (W x H x D) : 357.23 x 127.66 x 20.71 mm Box Dimension (W x H x D) : 440 x 290 x 92 mm
Weight (Est.)	Net Weight with Stand : 0.95 Kg Gross Weight : 2.3 Kg
Accessories	Power Adaptor, USB-C cable (optional), HDMI cable (optional), USB-C to USB-A Cable (optional), USB-C to USB-A adaptor (optional), Calibration Report, Quick Start Guide, Warranty Card, ProArt Sleeve
Compliance Standard	Energy Star®, FCC, UL/cUL, CB, CE, ErP, WEEE, BSMI, RCM, VCCI, J-MOSS, KCC, BIS, RoHS, CEC, WHQL Windows 7/10/11, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified

* Power Consumption is measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice

