


ProArt Display PA279CRV



Key Features



4 times the resolution of full HD 1080p with HDR-10 for stunning details and image quality



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



provides brighter imagery and supports the cinema-standard 99% DCI-P3 color gamut



Designed to encompass most of the colors achievable on CMYK color printers



Factory pre-calibrated to guarantee the ΔE color difference less than 2



Full function USB-C connection for DisplayPort video, USB data transmission and supports 96W power delivery



Daisy-chain

DisplayPort allows users to daisy chain up to 4 monitors for a multi-display workstation from one video source



USB Hub

Embedded four USB ports for connecting mouse, keyboard, or other USB devices



4-way Ergonomic Stand

Ergonomically-designed stand with tilt, swivel, pivot, and height adjustments

ASUS

ProArt Display PA279CRV

Spec Sheet

Display	Panel Size : 27-inch (68.47cm) Wide Screen (16:9) Display Viewing Area(HxV) : 596.73 x 335.66 mm Display Surface : Non-Glare Panel Type : IPS Viewing Angle (CR≥10, H/V) : 178° / 178° Pixel Pitch : 0.155 mm Resolution : 3840x2160 Color Space (sRGB) : 100% Color Space (Rec. 709) : 100% Color Space (Adobe RGB) : 99% Color Space (DCI-P3) : 99% Brightness (Typ.) : 300cd/m ² Brightness (HDR, Peak) : 400cd/m ² Contrast Ratio (Dynamic) : 3000:1 Contrast Ratio (Typ.) : 1000:1 Display Colors : 1073.7M (10 bit) Response Time : 5ms (GTG) Refresh Rate (Max) : 60Hz HDR (High Dynamic Range) Support : HDR-10 Flicker-free : Yes	
Video Feature	ProArt Preset : Native / sRGB / Rec. 709 / DCI-P3 / Adobe RGB / Rec. 2020 / DICOM / HDR / User Mode 1 / User Mode 2 Color Temp. Selection : Yes (5 modes) Color Adjustment : 6-axis adjustment (R,G,B,C,M,Y) Gamma adjustment : Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes PiP/PbP : Yes QuickFit : Yes (Paper / Alignment Grid / Ruler) HDCP : Yes, 2.2 VRR Technology : Adaptive-Sync (48~60Hz) Low Blue Light : Yes	
Audio Feature	Speaker : Yes (2Wx2)	
IO ports	USB-C x 1 DisplayPort 1.4 x 2 (Daisy Chain) HDMI(v2.0) x 2 USB Hub : Yes (USB 3.2 Gen 1 Type-C; USB 3.2 Gen 1 Type-A x 3) Earphone Jack : Yes USB-C Power Delivery : 96W DisplayPort1.4 DisplayPort1.4 (MST)  HDMI (v2.0) HDMI (v2.0) USB-C Earphone Jack USB Hub	
Signal Frequency	Digital Signal Frequency : 15~135 KHz (H) / 48~60 Hz (V)	
Power Consumption	Power On (Typical): < 17.78W Power Saving Mode : < 0.5W ; Power Off Mode : 0W (Hard Switch) 100-240V, 50/60Hz	
Mechanical Design	Tilt : Yes (+23° ~ -5°) Swivel : Yes (+30° ~ -30°) Pivot : 90° (Clockwise& Anticlockwise) Height Adjustment : 0~130mm VESA Wall Mounting : 100x100mm Kensington Lock : Yes	
Dimensions (Est.)	Phys. Dimension with Stand (W x H x D) : 612.22 x (408.11~538.11) x 215 mm Phys. Dimension without Stand (W x H x D) : 612.22 x 362.89 x 44.1 mm Box Dimension (W x H x D) : 691 x 427 x 138 mm	
Weight (Est.)	Net Weight with Stand : 5.78 Kg Net Weight without Stand : 4.07 Kg Gross Weight : 8.69 Kg	
Accessories	Power cord, USB-C cable (optional), HDMI cable (optional), DisplayPort cable (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card	
Compliance Standard	cTUVus, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, CCC, CEL, CECP, BSMI, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, SDoC, e-Standby, PSB, VN MEPS, Energy Star, TCO, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold, TÜV Flicker Free, TÜV Low Blue Light, VESA DisplayHDR 400, VESA MediaSync Display, Calman Verified, Mac compliance	

*Power consumption is measured with screen brightness of 200 nits without audio / USB / or other peripheral connections drawing power.

**All specifications are subject to change without notice

