## **TUF GAMING VG34VQL3A MONITOR**



## **KEY FEATURES**

**WQHD** 3440x1440 Wide QHD crystal image quality with HDR effect

180<sub>Hz</sub> Rapid Refresh

High refresh rate for ultra fast and smooth gameplay



Curved Design

1500R for immersive and captivating gaming experience



With DisplayHDR™ 400 certification to Visa Centrico 400 Centrico DisplayHDR\* 400 reproduce lifelike images

1ms response time (GTG) for sharp gaming visuals with high frame rates



**Shadow Boost** 

To enhance the details in dark scenes



Support wide color gamut to reproduce vivid color

**∆DMA** FreeSync Premium Pro

Eliminates smearing and tearing, allowing you to smoothly react to your game



Extreme Low **Motion Blur** 

**Enables ELMB** eliminating ghosting and tearing for sharp gaming visuals



TUF Gaming VG34VQL3A has undergone stringent performance tests and is certified Flicker-free and Low Blue Light (Hardware solution) by TÜV Rheinland laboratories, a global provider of technical, safety, and certification services.



THE CAMING VC34VOL3A MONITOR

IUF	Panel Size (diagonal)	34" Ultra Wide Screen (21:9)
Display	Display Viewing Area	797.22x333.72 mm
	Panel Backlight/ Type	WLED/VA
	Display Surface	Non-glare
	Curvature	1500R
	True Resolution	3440 x 1440
	Pixel Pitch	0.232mm
	Brightness (typical)	400 cd/m2
	Contrast Ratio (Max.)	4,000:1
	Viewing Angle (CR≥10)	178°(H) / 178°(V)
	Color saturation	125% sRGB
	Display Colors	16.7M
	Response Time	1ms GTG
	Refresh rate	180Hz
	Flicker Free	Yes
	HDR	VESA DisplayHDR 400
	Multiple HDR mode	Yes
Video Features	ELMB technology	Yes
	HDCP	Yes
	GameVisual	Yes (FPS,RTS/RPG, Racing , sRGB, Cinema, Scenery, MOBA)
	GamePlus	Yes (Crosshair, Timer, FPS Counter, Display Alignment, Stopwatch)
	GameFast Input technology	Yes
	Low Blue Light	Yes
Input / Output		2 x HDMI (v2.0) 2 x DisplayPort 1.4 3.5 mm earphone-jack 3 x USB 3.2 Gen 2 Type-A
Speaker	The state of the s	2W x 2 stereo, RMS
Signal Frequency		HDMI: 30~149 KHz (H) / 48~100Hz (V) DP: 267~267 KHz (H) / 48~180Hz (V)
Power	Power Consumption	<27W*
	Power Saving mode	<0.5W
	Power Off mode	<0.3W
	Voltage	100–240V, 50 / 60 Hz
Mechanical Design	Tilt	+20° ~ -5°
	Swivel	+10° ~ -10°
	Height adjustment	0~130mm
Dimension	Phy. Dimension	808 x (411 ~ 541) x 250 mm (with stand) 808 x 364 x 111 mm (without stand) 915 x 495 x 280 mm(box)
Weight	8.1 kg (net), 5.8 kg (net without stand), 11.3 kg (gross)	
Special Features	Variable OD, Shadow Boost, ELMB, FreeSync Premium Pro, DisplayWidget Center, Tripod socket	
Accessories	Power cord, Warranty card , QSG, HDMI cable(option), DP cable(option), USB cable (option)	
Compliance and Standards	TUV-Flicker Free, TUV-Low Blue Light, FSC Mixed	

<sup>\*1</sup>ms GTG spec is based on internal testes. Response time may vary depending on test conditions \*\* measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection