

MultiSync® P754Q

LCD 75" Ultra-High Definition Large Format Display

Preliminary Datasheet

The Definition of Digital Signage

Modular and scalable, NEC's MultiSync® P754Q display brings powerful capability for best-in-class large screen visualisation. Deliver your message with impact and seamless simplicity for the most convincing results.

Stunning UHD "pixel-free" ergonomic viewing is smartly merged with reliable colour reproduction for the most realistic and thrilling images with expanded contrast ratios. Compelling readability even in bright ambient light conditions is guaranteed with high brightness levels of 700 cd/m² combined with an anti-glare surface. Its modern, slim design forms an elegant digital surface which perfectly complements the surrounding architecture and integrates seamlessly into any environment. The Open Modular Intelligence (OMi) approach provides tailor-made signage solutions, where scalable computing power such as Raspberry Pi compute modules or OPS Slot-in PCs are seamlessly embedded into the display.

The 75" MultiSync® P754Q is the ultimate expansive choice for large visual surfaces in bright retail environments, passenger information and other public spaces as well as for colour critical reference applications in science, media and control rooms.

Benefits

Superb readability in bright light environments – crisp playback of content thanks to high brightness output of 700 cd/m² and anti-reflective screen surface delivers clearly visible messages even under varying and demanding ambient conditions.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Future-proof signal connectivity and processing – numerous native UHD resolution inputs with 60Hz refresh rate including DisplayPort, HDMI and an option slot for OPS Slot-in PCs, plus automatic upscaling to UHD for other signals, provide "pixel-free viewing" on a large scale.

Future Ready with Open Modular Intelligence Expansion – upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute modules or signal interfaces for content feed and computing.

Enhanced imaging performance – advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the Spectraview Engine for precise, natural images.

Modern and slim design – robust yet elegant allowing for an unobtrusive integration into any application and environment.

Cost Saving Device Management – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

Product Name	MultiSync® P754Q
Product Group	LCD 75" Ultra-High Definition Large Format Display
Order Code	60004316

Display

Panel Technology	IPS with Edge LED backlights
Active Screen Area (W x H) [mm]	1,649.7 x 927.9
Screen Size [inch/cm]	75 / 189
Brightness [cd/m ²]	650, 450 (shipment setting)
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)

Response Time (typ.) [ms]	8 (grey-to-grey)			
Haze Level [%]	Pro (28)			
Supported Orientation	Face Up; Landscape; Portrait			
Synchronisation Rate				
Horizontal Frequency [kHz]	31.5 - 91.1			
Vertical Frequency [Hz]	24 - 85			
Resolution				
Native Resolution	3840 x 2160			
Supported Resolutions	4096 x 2160;	3840 x 2160;	1920 x 2160;	1920 x 1080
Connectivity				
Input Video Digital	2 x DisplayPort (with HDCP); 3 x HDMI (with HDCP)			
Input Audio Analogue	1 x 3,5 mm jack			
Input Audio Digital	2 x DisplayPort; 3 x HDMI			
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232			
Input Data	1 x microSD (Value); 1 x USB 2.0 (Downstream); 1 x USB 2.0 (MediaPlayer); 1 x USB Type-B (Upstream); 2 x USB 2.0 (Compute Module, 1 x 5V/2A powered)			
Output Video Digital	1 x DisplayPort (loop through: DisplayPort, OPS slot-in PC)			
Output Audio Analogue	1 x 3,5 mm jack			
Output Control	1 x LAN 100Mbit			
Open Modular Intelligence				
OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)			
OPS Max. Current / Power Consumption [A / W]	4 / 58			
Compute Module Slot	Slot Technology: Compute Module Slot (NEC proprietary standard)			
Sensors				
Ambient Light Sensor	Integrated, triggered actions programmable			
Human Sensor	Optional, external, 4-5m range, triggered actions programmable			
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable			
NFC Sensor	Integrated, 2cm range, free NEC Android App required			
Electrical				
Power Consumption [W]	195 shipping			
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)			
Power Management	VESA DPMS			
Environmental Conditions				
Operating Temperature [°C]	+0 to +40			
Operating Humidity [%]	20 to 80			
Mechanical				
Dimensions (W x H x D) [mm]	Without stand: 1,681 x 960 x 71			
Weight [kg]	53			
Bezel Width [mm]	14.8 (left and right); 14.8 (top and bottom)			
VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); 600 x 400 (FDMI); M8			

Additional Features

Special Characteristics	12-bit Look Up table; Ambient Light Sensor; AMX NetLinx Support; ASCII Control Commands; Auto ID assignment; Auto tiling function; Automated Email Alert; CEC Support; Crestron Connected Support; DICOM support; Display Browser Control; Emergency Notification; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2; OmniColor Control; OSD rotation for portrait mode; PIN as theft protection; PJLink Support; Powered USB-Port; Removable Logo; Scheduler; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10); User readable log function
Colour Versions	optional coloured overframes
Safety and Ergonomics	CE; EAC; EMC Class B; FCC; SASO; TÜV GS; UL/C-UL or CSA; VCCI
Audio	Integrated Speakers (10 W + 10 W); Optional Speakers (15 W + 15 W)
Shipping Content	CD-ROM (User Guides/Manuals); Display; DisplayPort Cable; Remote Control; USB cable
Warranty	3 years warranty incl. backlight; optional 4. + 5. year warranty extension
Operating Hours	24/7

Available Options

Accessories	Feet (ST-801); Speaker (SP-754QSM, SP-TF1); Trolley (PD02MHA, PD03MHA, PDMHM-L); Wall mount (PDW T XL-2)
Compute Module Slot	NEC Compute Module; Raspberry Pi Compute Module 1 and 3
OPS Slot	HDBaseT receiver; Intel® Atom, Celeron and Core CPUs; OPS-2C Quad 3G SDI

MediaPlayer

Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000
Supported Video Formats	MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz
Supported Audio Formats	MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling
Supported File Storage / File System	MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 314 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: B; Local dimming
-------------------	---



CE



TÜV GS



VCCI

This document is © 2018 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 01.06.2018