

TM-Series LED-backlit Display 22" | 23"



Crafted with advanced projected capacitive 10-point touch technology, the TM-Series not only delivers smooth and precise touch response, but also enables more creative and exciting interactive applications. Delivering seamless compatibility with Windows® 7, 8 & 10 touch functions, the Full HD resolution and versatile connectivity make it easily connected with media source and peripheral devices. Its height adjustability and tilt flexibility ranging from –5 to 90 degrees guarantee ergonomic-friendliness and multi-user comfort, making it a value choice for public and interactive environments.













10-Point Multi-Touch Stylish Display

Based on Projected Capacitive Touch Technology, the TM-Series provides 10-point touch capability and boosts pointing precision significantly with seamless touch sense. With a true flat surface and edge-to-edge glass overlay, the TM-Series offers an invitingly modern appeal that fits the professional environments.

Maximise Multi-user Comfort

With a flexible dual-hinge stand, the TM-Series provides height adjustability and a wide tilt range from -5° to 90° that optimise multi-user comfort and productivity. Given a wide (178°) viewing angle*, it allows multiple users to comfortably share a single display at the same time.







Easy Integration

10-point touch capability plug and play for systems with Windows 7/8/10 and versatile connectivity, VGA, HDMI, DisplayPort, enable effortless system integration for creative and exciting interactive applications. The built-in USB Port (USB 3.0) also allows easy connection with peripheral devices

Features

- \bullet Full HD 1920 x 1080 resolution
- IPS Panel technology offers high colour accuracy and wide viewing angles (23" only)
- Flush touch screen makes surface neat and clean
- Versatile connectivity: DisplayPort, HDMI, VGA
- Incorporates projected capacitive touch technology
- Windows 10 ready plug and play support for Windows 7/8/10
- Built-in USB 3.0 Port for easy connection with storage devices
- Flicker-free display technology reduces eye discomfort
- Built-in speakers

- Kensington security slot
- VESA mount compatibility for flexible installation
- Flexible dual-hinge stand design to maximise viewing comfort for multiple users
- Tilt capacity from -5° to 90°
- * Product features may vary by models



THE DISPLAY CHOICE OF PROFESSIONALS

Specifications	TM-22	TM-23
Panel		
Panel Type	LED-Backlit TFT LCD (TN Technology)	LED-Backlit TFT LCD (IPS Technology)
Panel Size	21.5"	23.0"
Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
Pixel Pitch	0.248 mm	0.265 mm
Brightness	250 cd/m²	250 cd/m²
Contrast Ratio	20,000,000:1 (DCR)	20,000,000:1 (DCR)
Viewing Angle (H/V)	170°/160°	178°/178°
Display Colour	16.7M	16.7M
Response Time	3 ms	5 ms
Frequency		
Frequency (H)	30 kHz-83 kHz	30 kHz-83 kHz
Frequency (V)	50 Hz-76 Hz	50 Hz-76 Hz
Signal Input		
DisplayPort	x 1	x 1
HDMI	1.3 x 1	1.3 x 1
VGA	15-Pin D-Sub x 1	15-Pin D-Sub x 1
Other Connectivity	15 Thi D Sub X T	13 1 m B 800 K 1
USB	USB HUB (3.0 x 4)	USB HUB (3.0 x 4)
Audio	355 1.55 (5.0 K I)	352 .152 (5.0 K I)
Audio In	Stereo Audio Jack /3 5 mm)	Stereo Audio Jack (3.5 mm)
Internal Speakers	Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 mm) 2W x 2
Touch Screen	ZW AZ	∠w A∠
Panel Interface	IICR /Type_R\	IICR /Tuma-R\
	USB (Type-B)	USB (Type-B)
Technology	Projective Capacitive	Projective Capacitive
Positional Accuracy	± 1.0 mm	± 1.0 mm
Multi-touch Plug & Play	10-point touch for Windows 7/8/10	10-point touch for Windows 7/8/10
Single Touch Support by Driver	Windows XP	Windows XP
Power		
Power Supply	Internal	Internal
Power Requirements	AC 100-240V, 50/60 Hz	AC 100-240V, 50/60 Hz
On Mode	14W (On)	14W (On)
Stand-by Mode	< 0.5W	< 0.7W
Off Mode	< 0.3W	< 0.3W
Glass		
Thickness	2.4 mm (0.09")	2.4 mm (0.09")
Transmission Rate	> 90%	> 90%
Hardness	> 7H	> 7H
Operating Conditions		
Temperature	0°C-40°C (32°F-104°F)	0°C-40°C (32°F-104°F)
Humidity	10%-85% (non-condensing)	10%-85% (non-condensing)
Storage Conditions	10% 05% (Holf Collactioning)	10/0 03/0 (Holi colideliania)
Temperature	-25°C-55°C (-13°F-131°F)	-25°C-55°C (-13°F-131°F)
•		
Humidity	5%-93% (non-condensing)	5%-93% (non-condensing)
Mounting	Vog (100 v 100 mm)	Voc (100 v 100 mm)
VESA FPMPMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Stand	F0.4+ 000	F0.4+ 000
Tilt	-5° to 90°	-5° to 90°
Height Adjustment	122.0-387.4 mm	131.5-400.0 mm
Security		
Kensington Security Slot	Yes	Yes
Dimensions		
Product with Base (W x H x D)	522.4 x 387.4 x 238.5 mm (20.6" x 15.3" x 9.4")	561.0 x 400.0 x 238.5 mm (22.1" x 15.7" x 9.4")
Product w/o Base (W x H x D)	522.4 x 318.4 x 57.2 mm (20.6" x 12.5" x 2.3")	561.0 x 338.2 x 57.2 mm (22.1" x 13.4" x 2.3")
Packaging (W x H x D)	586.0 x 422.0 x 186.0 mm (23.1" x 16.6" x 7.3")	632.0 x 448.0 x 186.0 mm (24.9" x 17.6" x 7.3")
Weight		
Product w/o Base	3.9 kg (8.6 lb)	4.3 kg (9.5 lb)
Product with Base	6.3 kg (13.9 lb)	6.6 kg (14.6 lb)
Packaging	8.1 kg (17.9 lb)	8.7 kg (19.2 lb)
Regulation Approval		
Certifications & Compliance	FCC, CE, LVD, WEEE, RoHS, REACH, EAC	CE, FCC, LVD, BSMI, WEEE, RoHS, REACH, EAC
Accessories		
Supplied	Power Cord, VGA Cable, Audio Cable, USB Cable, Warranty Card, CD	Power Cord, VGA Cable, Audio Cable, USB Cable, Warranty Card, CD
Optional Accessories		
Wall Mount (Landscape only)	WMK-01, WMK-03, PMK-01	WMK-01, WMK-03, PMK-01



Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d Ijssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

www.agneovo.com

