

Camera G5 Dome



Mechanical

Dimensions	Ø 109.2 x 64.5 mm (4.3 x 2.5")
Weight	390 g (13.76 oz)
Enclosure materials	Aluminum alloy, polycarbonate, hard-coated dome
Mount materials	Polycarbonate, stainless steel
Weatherproofing	IPX4
Resistance	IK08

Optics

Sensor	5MP CMOS sensor
Lens	Fixed focal length
View angle	H: 102.4°, V: 71.4°, D: 134.3°
Night mode	Built-in IR LED illumination and IR cut filter

Video

Video compression	H.264, MJPEG
Resolution	2688 x 1512 (16:9)
Maximum frame rate	30 FPS
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor specs	Dual-core Arm® Cortex®-A7 based chip
Memory information	2 Gb
Management interface	UniFi Protect
Networking interface	10/100 MbE RJ45
Flash memory support	2 Gb
Max. power consumption	5W
Power requirements	PoE
Supported voltage range	37–57VDC
Link/activity LED	R/G/B/W
Button	Factory reset
Mounting	Wall, ceiling mount
Operating temperature	-20 to 40° C (-4 to 104° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

Audio

Microphone	Yes (can be disabled in software)
Speaker	Yes

Software

UniFi OS application	UniFi Protect
Mobile app	UniFi Protect iOS™ and Android™